




F110 FULLY RUGGED TABLET

- 11th Generation Intel® Core™ i7 / i5 vPro® Processor
- Thunderbolt™ 4 brings lightning speed and performance
- Enhanced enterprise security with optional Intel® vPro®, Windows Hello face-authentication camera, TPM 2.0 and many more multi-factor authentication options
- Configurable options to fit diverse data collection needs: Optional 1D/2D imager barcode reader / USB 2.0 port / Serial port + LAN port (RJ45)
- LifeSupport™ battery swappable technology



F110 3D demo



SPECIFICATIONS

Generation

G6

Operating System

Windows 11 Pro

Mobile Computing Platform Options

Intel® Core™ i5-1135G7 Processor
Max. 4.2GHz with Intel® Turbo Boost Technology
- 8MB Intel® Smart Cache

Platform options:

Intel® Core™ i5-1145G7 vPro® Processor
Max. 4.4GHz with Intel® Turbo Boost Technology
- 8MB Intel® Smart Cache

Intel® Core™ i7-1165G7 Processor
Max. 4.7GHz with Intel® Turbo Boost Technology
- 12MB Intel® Smart Cache

Intel® Core™ i7-1185G7 vPro® Processor
Max. 4.8GHz with Intel® Turbo Boost Technology
- 12MB Intel® Smart Cache

VGA Controller

Intel® UHD Graphics

Display

11.6" Wide Viewing Angle TFT LCD FHD (1920 x 1080)

Protection film

1,000 nits LumiBond®

display with Getac sunlight readable technology

Capacitive multi-touch screen

Storage & Memory

8GB DDR4

Optional: 16GB / 32GB DDR4

256GB PCIe NVMe SSD

Optional: 512GB / 1TB / 2TB PCIe NVMe SSD

Keyboard

Power button

4 tablet programmable buttons

Pointing Device

Touchscreen

- Capacitive multi-touch screen

- Optional: Dual mode touchscreen (multi-touch and digitizer)

Expansion Slots

Optional: Smart card reader

Optional: 1D/2D imager barcode reader, or USB 2.0 port, or LAN (RJ45), or serial port + LAN (RJ45)ⁱ

Optionalⁱⁱ: HF RFID Reader, or Fingerprint Reader

I/O Interface

5M webcam x 1ⁱⁱⁱ

8M pixels auto focus rear camera x 1

Audio in/out combo x 1

DC in Jack x 1

Thunderbolt™ 4 Type-C x 1

USB 3.2 Gen 2 Type-A x 1

Docking connector x 1

Optional: SIM card slot x 1 (Micro-SIM, 3FF)^{iv}

Optional: Windows Hello face-authentication FHD camera (front facing) x 1ⁱⁱⁱ

Optional: RF antenna pass-through for GPS, WWAN and WLAN

Communication Interface

Intel® Wi-Fi 6 AX201, 802.11ax

Bluetooth (v5.2)^v

Optional: 4G LTE mobile broadband with integrated GPS^{iv}

Optional: 10/100/1000 base-T Ethernetⁱ (Occupies expansion slot)

Optional: 5G Sub-6 with integrated L1/L5 GPS^{vi, xv}

Security Features

TPM 2.0

Kensington lock

Optional: Intel® vPro® Technology

Optional: HF RFID Reader^{ii, vii}, or Smart Card Reader, or Fingerprint Readerⁱⁱ

Optional: Windows Hello face-authentication FHD camera (front-facing)ⁱⁱⁱ

Power

AC adapter (90W, 100-240VAC, 50/60Hz)

Li-ion battery (11.4V, typical 2680mAh; min. 2640mAh) x 2

LifeSupport™ battery swappable technology

Optional: High capacity Li-ion battery (11.1V, typical 4200mAh; min. 4080mAh) x 2

Dimension (W x D x H) & Weight

314 x 207 x 25mm (12.4" x 8.15" x 0.98")

1.52kg (3.35lbs)^{viii}

Rugged Features

MIL-STD-810H certified

IP66 certified

MIL-STD-461G certified^{ix}

Vibration & 6ft (1.8m) drop resistant

Optional: ANSI/UL 121201, CSA C22.2 NO. 213 (Class I, Division 2, Groups A, B, C, D)^x

Environmental Specifications

Temperature^{xii}:

- Operating: -29°C to 63°C / -20°F to 145°F

- Storage: -51°C to 71°C / -60°F to 160°F

Humidity: - 95% RH, non-condensing

Pre-installed software

Getac Utility

Getac Camera

Getac Geolocation

Getac Barcode Manager^{xiii}

Getac Driving Safety Utility (trial version)

Getac KeyWedge Barcode Reader Utility (trial version)

Optional: Absolute Persistence^o

Optional software

Getac Driving Safety Utility

Getac KeyWedge Barcode Reader Utility

Getac Device Monitoring System (GDMS)

Getac VGPS Utility^{xiiii}

Accessories

Battery (11.4V, typical 2680mAh; min. 2640mAh)

AC adapter (90W, 100-240VAC, 50 / 60Hz)

Capacitive stylus with tether

Optional:

Carry bag

Battery (11.4V, typical 2680mAh; min. 2640mAh)

High capacity Li-ion battery (11.1V, typical 4200mAh; min. 4080mAh)

Multi-Bay charger (Dual-Bay)

Multi-Bay charger (Eight-Bay)

AC adapter (90W, 100-240VAC, 50 / 60Hz)

Office dock AC adapter (90W, 100-240VAC)

MIL-STD-461 AC adapter (90W, 100-240VAC)

DC-DC vehicle adapter (120W, 11-32VDC)

Digitizer pen

Capacitive stylus with tether

Protection film

Hard handle

Hand strap

Shoulder strap (2-point)

Shoulder harness (4-point; handsfree)

Detachable keyboard

Vehicle cradle^{xv}

Vehicle dock^{xvi}

Office dock

Spare SSD kit

100W Type-C adapter

Getac rugged keyboard

Bumper-to-Bumper warranty

Accidents can take your equipment out of service when you least expect it, especially in a rugged environment, which can cause costly equipment downtime.

That is why Getac has introduced accidental damage as standard under our Bumper-to-Bumper warranty, to help minimize your enterprise IT costs. Bumper-to-Bumper is your hassle-free guarantee.

That means you can depend on us to have your unit back in service within days.

Standard

3 years Bumper-to-Bumper

F110 FULLY RUGGED TABLET

- I. 1D/2D imager barcode reader, or USB (USB 2.0) port, or Serial port + LAN are mutually exclusive options.
- II. HF RFID reader and fingerprint reader are mutually exclusive options
- III. 5M webcam and optional Windows Hello face-authentication FHD camera (front-facing) are mutually exclusive options.
- IV. Units with 4G LTE option comes with an embedded SIM card slot.
- V. Bluetooth performance and connectable distance may be subject to interference with the environments and performance on client devices, users may be able to reduce effects of interference by minimizing the number of active Bluetooth wireless devices that is operating in the area.
- VI. One physical SIM card slot and one eSIM. Network service may vary depending on local telecommunication providers.
- VII. 13.56MHz HF RFID reader (ISO 15693, 14443 A/B, Mifare and FeliCa™ compliant).
- VIII. Weight and dimensions vary from configurations and optional accessories; optional high-capacity batteries add approx. 6mm (H), 0.24kg.
- IX. MIL-STD-461 90W AC adapter sold separately.
- X. Available with limited configurations and environment conditions.
- XI. Tested by an independent third-party test lab following MIL-STD-810H.
- XII. Available when barcode reader option is selected.
- XIII. Models require either embedded or standalone GPS module.
- XIV. Gamber Johnson and Havis vehicle docks are e-mark certified.
- XV. Support GPS, GLONASS, Galileo, BeiDou and QZSS.

Information provided herewith is for reference only, available specification shall be subjected to quotation by request.

	Vehicle Dock	Office Dock
Serial Port	2	2
External VGA	1	1
Microphone	1	1
Audio Output	1	1
DC in Jack	1	1
USB	4	4
LAN	1	1
HDMI	1	1
RF Antenna Connector	3 (WWAN, WLAN, GPS)	-

Getac



Getac USA

15495 Sand Canyon Ave. Suite 350 Irvine, CA 92618 Tel : 949-681-2900

GetacSales_US@getac.com |

www.getac.com/us/ Copyright © 2022 Getac Technology Corporation and/or any of its affiliates. All Rights Reserved. Information provided herewith is for reference only, available specification shall be subjected to quotation by request.